



Maxiprop												Megaprop															
TR215.xx-6/8	TR215.xx-4/8V	TR215.xx-4/8	TR215.xx-4/12	TR221.xx-8/8	TR221.xx-6/8	TR221.xx-4/8V	TR221.xx-4/8	TR221.xx-4/12	TR226.xx-8/8	TR226.xx-6/8	TR226.xx-4/8V	TR226.xx-4/8	TR226.xx-4/12	TR315.xx-6/8	TR315.xx-4/8V	TR315.xx-4/8	TR315.xx-4/12	TR321.xx-8/8	TR321.xx-6/8	TR321.xx-4/8V	TR321.xx-4/8	TR321.xx-4/12	TR326.xx-6/8	TR326.xx-4/8	TR326.xx-4/12	(TR326.xx-4/16)	
2	2	2	2	2	2	2	2	2	2	2	2	2	2	3	3	3	3	3	3	3	3	3	3	3	3	3	
GRP	GRP	GRP	GRP	GRP	GRP	GRP	GRP	GRP	GRP	GRP	GRP	GRP	GRP	GRP	GRP	GRP	GRP	GRP	GRP	GRP	GRP	GRP	GRP	GRP	GRP	GRP	
1500	1500	1500	1500	2050	2050	2050	2050	2050	2600	2600	2600	2600	2600	1500	1500	1500	1500	2050	2050	2050	2050	2050	2600	2600	2600	2600	
17	26	40	53	25	33	41	46	57	20	29	35	41	46	17	26	40	44	23	33	36	41	49	26	31	41	45	
24	40	44	57	32	39	45	53	59	27	32	39	43	46	24	38	40	44	31	35	39	45	52	30	39	43	47	
1.75	2.50	3.50	4.50	1.10	1.75	2.50	3.50	4.50	1.10	1.75	2.50	3.50	4.50	1.75	2.50	3.50	4.50	1.10	1.75	2.50	3.50	4.50	1.75	3.50	4.50	6.50	
0.60	0.90	2.50	4.90	0.60	1.20	1.70	2.50	4.20	0.68	1.36	2.48	2.52	3.65	0.60	1.10	3.40	4.60	0.70	1.50	1.80	2.50	4.00	1.74	2.20	4.42	6.11	
0.80	2.50	3.30	5.80	1.10	1.70	2.00	3.70	4.90	1.19	1.82	3.13	4.01	4.89	0.90	3.10			1.30	1.80	2.30	3.20	4.90	2.08	3.92	4.98	6.41	
300	700	1420	2400	650	1200	1850	2200	3400	800	1670	2620	2640	3440	450	830	1920	2450	750	1450	1800	2250	3250	2040	2330	4030	5080	
630	1420	1700	2560	1100	1700	2150	2900	3650	1430	2110	3060	3670	4370	750	1780			1300	1650	2100	2700	3700	2260	3600	4340	5270	
172	172	172	182	178	178	178	178	188	177	177	177	177	187	190	190	190	200	199	199	199	199	209	197	197	207	218	
++	++	++	++	++	++	++	++	++	++	++	++	++	++	++	++	++	++	++	++	++	++	++	++	++	++	++	++
++	++	++	++	++	++	++	++	++	++	++	++	++	++	++	++	++	++	++	++	++	++	++	++	++	++	++	++
++	++	++	++	++	++	++	++	++	++	++	++	++	++	++	++	++	++	++	++	++	++	++	++	++	++	++	++
-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
+	+	+	+	++	++	++	++	++	+	+	+	+	++	++	++	++	++
+	+	+	+	+	+	+	+
+	+	+	+	++	++	++	++	++	+	+	+	+	+	+	+	+	+	++	++	++	++	++	+	+	+	+	+
+	+	.	.	+	+	+	.	.	+	+	+	.	.	+	+	.	.	+	+	.	.	+	+
++	++	++	++	++	++	++	++	++	++	++	++	++	++	++	++	++	++	++	++	++	++	++	++	++	++	++	++
1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1

High-efficiency submersible mixers.
 Made by Wilo.
 Up to 10% energy cost savings.
 The newest generation.



EMU
Technologie

Wilo-EMU Megaprop TR 326.

Wilo presents their newest and most efficient generation of mixers. Due to an innovative blade shape and a propeller diameter of 2.60 m, our low-speed mixers achieve the best thrust values with the most favourable performance factors (ISO 21630). For the first time, the thrust performance factor gives you the opportunity of an objective comparison with similar submersible mixers. The result: up to 10% lower energy costs. A conversion will therefore pay for itself within a very short time. Extremely durable one-piece GRP laminated blades ensure maximum periods of use and minimum maintenance costs.

Excellent? We call that Pumpen Intelligenz.

www.wilo.com



Send us the data on your water treatment system and we will make an individual offer for you! You will receive your own special configuration – energy-efficient, economic and reliable!

Send a fax to Wilo +49 9281-96528



Company: _____
 City: _____
 Country: _____
 Name: _____
 Fax: _____

With the request for
 a selection
 a price offer

Date: _____
 Signature: _____

1. Selection data	item
1.1 Application	
1.2 Aeration	<input type="checkbox"/>
1.2.1 Kind of aeration	
1.2.2 Air input	m ³ N/h
1.2.3 Aerated surface*	m ²
1.3 Kind of liquid	
1.3.1 pH-value*	
1.3.2 Solids content	%
1.3.3 Temperature	°C
1.3.4 Density*	kg/m ³
1.3.5 Viscosity*	mPas
1.3.6 Kind of thickening*	
1.4 Tank dimensions* ¹	
1.4.1 Length x width	m x m
1.4.2 Diameter	m
1.4.3 Liquid depth	m
1.4.4 Tank depth	m
1.5 Tank materials	
1.5.1 Concrete	<input type="checkbox"/>
1.5.2 Steel	<input type="checkbox"/>
1.5.3 Others	
1.6 Medium flow velocity	m/s

2. Technical data	
2.1 Voltage	~ 3 / V / Hz
2.2 Starting	
2.2.1 Direct	<input type="checkbox"/>
2.2.2 Star-delta	<input type="checkbox"/>
2.2.3 Others	
2.3 Motor control	
2.3.1 Winding	<input type="checkbox"/>
2.3.2 Sealing chamber control	<input type="checkbox"/>
2.3.3 Others	
2.4 Ex protection	<input type="checkbox"/>
2.5 Max. starts per hour	/h
2.6 Power cable: length	m

3. Further information

* if available ¹ enclose sketch